



COMBI ELASTIC S-3000 N25



Adjustable height: 70 mm. Natural frequency = 25 Hz.

Granab subfloor system COMBI ELASTIC S-3000 N25 is constructed according to the above section. The system is very resistant to high loads and meets the requirements of C5 according to Eurocode EN1991-1-1. A sports mat with combi-elastic properties or a sports parquet, for example, can be laid on top of the double floor chipboard. The highest requirement for combi-elastic sports floors according to EN Norm 14904:2006 Type C4 is easily achieved with this system.

The system's natural frequency = 25 Hz.

A SPORTS MAT

B FLOORBOARDS
2x22 mm chipboards.

C GIRDER
Granab system 3000 N25 Sport.
Galvanised steel.

D DAMPENING ELEMENT
25 mm sylodyn

E BLOCK WITH
ADJUSTMENT SCREW
70 mm.

EXAMPLE OF TEST RESULTS WITH SPORTS MATS P1/P2

Measurement	Test results	Requirements according to EN
Shock absorption	67 %	>55-75
Vertical deformation	3,6 mm	Max 5,0 mm
Vertical ball behaviour	93 %	Min 90 %



CERTIFYING
KONTROLL



Address
Åkerigatan 2 | S-447 37 Vårgårda | Sweden



E-mail
epost@granab.se



Telephone
+46 (0) 322-66-76-50